

Ambulance/Fire and Rescue Van and Cutaway Chassis

Power, performance and reliability at your disposal when everything is on the line.



When your job involves managing life-or-death situations, you need to have absolute confidence that your vehicle will be able to perform at a moment's notice. Chevrolet and GMC HD trucks and vans are ideal for emergency use and are built to meet your extreme service needs. With varying body styles, wheelbases and powertrain options backed by GM's 5-year/100,000-mile Transferable Powertrain Limited Warranty¹ — you can have confidence that your Chevrolet or GMC vehicle will be ready to move when you are. For more information visit gmfleet.com.

DIESEL ENGINE ON CUTAWAYS AND VANS

- Chevrolet/GMC offers clean, powerful and efficient 6.6L Turbo Diesel V8
- Diesel Particulate Filter
- Diesel Exhaust Fluid for NOx
- While others have discontinued diesel offerings, the Duramax diesel is available on cutaways, vans and cab chassis
- Diesel torque advantage over gas—maximum torque at low engine speed
- Diesel energy density is higher than gasoline, making diesel engines more efficient per gallon of fuel burned
- With direct fuel injection there is little wasted or unburned fuel

AVAILABLE AND STANDARD AMBULANCE PACKAGE OPTIONS²

- HD 6-speed transmission
- HD locking rear differential
- 33- and 57-gallon fuel tanks on cutaway models
- 3.73 rear axle ratio
- Dual-note horn
- HVAC system auxiliary provisions
- Dual 145-amp alternators
- Dual 770 CCA batteries
- Chrome appearance package
- High idle switch
- Dual rear wheels
- LED light package with separate stop/turn circuits
- Cold-climate options—engine block heater, auxiliary fuel-fired heater, engine cover

ALL-DAY RIDING COMFORT, CONVENIENCE AND PEACE OF MIND

- Exceptional handling and ride provided by long arm, short arm independent front suspension
- Rear hypoid drive axle with multileaf springs
- Available with factory-installed power seats
- Available with remote keyless entry and starter system
- Cruise control
- 3-Year/36,000-Mile Bumper-to-Bumper Warranty³
- 5-Year/100,000-Mile Transferable Powertrain Limited Warranty¹
- Onboard Wi-Fi available from Autonet.com

To learn more, visit gmfleet.com



¹Whichever comes first. See dealer for limited warranty details. The 2011 and 2012 model year 5-year/100,000-mile powertrain coverage applies to Chevrolet, Buick, Cadillac and GMC.

²See Order Guide for complete details/availability by model.

³Whichever comes first. See dealer for details.

mullen

Job #	GMC1-FCO-12-05166 — 378		Version #	3	Document Name	GMC1-FCO-12-05166-378 AMB Hero Card_v3.indd		Last Modified	6-12-2012 2:02 PM			
Job Description	Ambulance Hero Card		Art Director	anelson		Linked Graphics		Colors In-Use	User	Printer	Output Date	
Bleed	11.25" x 8.75"	Mech Scale	100	Copy Writer	n/a		47871-10_rech_100421a_123peopleV8.psd	CMYK	848 ppi	ma-jforza-mac	ATLANTIS	6-12-2012 4:41 PM
Trim	11" x 8.5"	Print Scale	None	Proj Mgr	csenn		313023Beaufort.jpg	RGB	401 ppi	Mechd By: None	RTVd By: None	
Live	10.5" x 8"	Stock	None	Acct Svc	kdenmark		gm_stripes_half_tineline.ai					
Folded Size	None			Prod Mgr	M. Gardner		GM_FCO_Primary_Divisional.ai					
Finishing	None			Art Buyer	NA		11F65Y00512.jpg	RGB	596 ppi			
Colors Spec'd	4C			Copy Edit	TBD		3500AMBARGOPIC.tif	CMYK	519 ppi			
Special Instr.	None			Mac	sforza		3500AMBPKC.tif	CMYK	519 ppi			
Publications	None						Amb450pic.tif	CMYK	519 ppi			

BY SENDING YOUR INITIALS ABOVE, YOU ARE STATING THAT YOU HAVE READ AND APPROVED THIS WORK.



Cargo 3500
G33705

Cutaway 3500
G33503/G33803

Cutaway 4500
G33803



Powertrain/Mechanical

Engine	Duramax 6.6L Turbo Diesel V8 (LGH)	Duramax 6.6L Turbo Diesel V8 (LGH)	Duramax 6.6L Turbo Diesel V8 (LGH)
Base transmission	MYD 6-Spd	MYD 6-Spd	MYD 6-Spd
Horsepower @ rpm	260 @ 3,100	260 @ 3,100	260 @ 3,100
Torque ft.-lbs. @ rpm	525 @ 1,600	525 @ 1,600	525 @ 1,600
Axle ratio	3.54	3.73	3.73
Standard battery	Dual 770 CCA	Dual 770 CCA	Dual 770 CCA
Alternator	Dual 145-amp	Dual 145-amp	Dual 145-amp
50-state emissions	FE9	FE9	FE9
Frame, yield strength (psi)	33,000	33,000	35,000
GCWR standard (lbs.) ¹	18,500	18,500	18,500
GVWR standard (lbs.) ²	9,900	12,300	14,200
GAWR (lbs.) front ¹	4,600	4,600	4,600
GAWR (lbs.) rear ¹	6,084	8,600	9,600
Curb weight (lbs.) ¹	6,411	5,657/5,716	6,043
Base payload (lbs.) ^{1,3}	3,438	6,591/6,532	8,135
Fuel tank capacity (gal.) ⁴	31	33/57	57
Standard tires	LT245/75R16E all-season blackwall	LT225/75R16E all-season blackwall	LT225/75R16E all-season blackwall
Wheels	SRW 16" x 6.5" 8-lug	DRW 16" x 6.5" 8-lug	DRW 16" x 6.5" 8-lug

Exterior Dimensions

Wheelbase (in.)	155	139/159	159
Overall length (OAL) (in.)	244.1	246.7/266.7	266.7
Overall height (in.)	82.8	82.9	82.9
Body width (in.)	79.2	79.1	79.1
Cab to axle (CA) (in.)	N/A	80/100	100
Cab to end of frame (CE) (in.)	N/A	148.5/168.5	168.5
Ground clearance front (in.)	8.8	7.6	7.6
Ground clearance rear (in.)	7.7	6.8	7.0
Turning diameter (C to C) (ft.)	54.5	43.4/54.5	54.5

AMBULANCE PACKAGES

YF2 (G33*33)

- 57-gallon rear tank⁴ (NE7) (33803 only)
- 3.73 rear axle (GT4)
- Duramax 6.6L V8 turbo diesel (LGH)
- Dual-note horn (U05)
- HVAC system auxiliary provisions (ENC)
- Chrome appearance package (ZR7)
- Dual 145-amp alternators (KD9)
- High idle switch (UF3)
- Dual rear wheels (R05)
- LED light package separate stop/turn circuits (V4D)
- HD locking rear differential (G80)

YF2 (G33705)

- Requires G33705 model
- Requires one of the following glass packages:
 - ZW2 rear doors fixed glass
 - ZW3 rear doors and side cargo doors fixed glass
 - ZW4 rear doors, side cargo door and rear passenger-side quarter fixed glass
 - ZW6 full-body window package fixed glass
- Includes (LGH) Duramax 6.6L Turbo Diesel V8 engine, (ZR7) Chrome appearance package, (U05) Dual-note horn, (G80) Heavy-duty locking rear differential, (KD9) Dual 145-amp alternator, (B31) Front only black rubberized vinyl floor covering, (ENC) HVAC system auxiliary provisions and (UF3) High idle switch



Fleet & Commercial
CHEVROLET • BUICK • GMC • CADILLAC

This material is not legally approved for use in any advertising. We have tried to make this brochure comprehensive and factual. We reserve the right to make changes at any time, without notice, in equipment, specifications, models and availability. Specifications, dimensions, measurements, ratings and other numbers in this brochure are approximate based upon design and engineering drawings and prototypes and laboratory tests. Your vehicle may differ due to variations in manufacture and equipment. See your local General Motors Fleet Account Executive or District Sales Manager for up-to-date information, or see the GM Online Order Guide at gmfleet.com.

Copyrights and Trademarks © 2012 General Motors. All rights reserved. Chevrolet, GMC, GM, the Chevrolet logo, GMC logo, GM logo, Chevy, Duramax and Vortec are trademarks of General Motors.

All text, images, graphics and other materials in this brochure are subject to the copyright and other intellectual property rights of General Motors. These materials may not be reproduced, distributed or modified without the express written permission of General Motors.

An important note about alterations and warranties: Installations or alterations to the original equipment vehicle (or chassis) as distributed by General Motors are not covered by the General Motors New Vehicle Limited Warranty. The special body company, assembler, equipment installer or upfitter is solely responsible for warranties on the body or equipment and any alterations (or any effect of the alterations) to any of the parts, components, systems or assemblies installed by GM. General Motors is not responsible for the safety or quality of design features, materials, or workmanship of any alterations by such suppliers.

¹ See Order Guide for complete details.

² Gross Vehicle Weight Rating (GVWR). When properly equipped, includes vehicle, passengers, cargo and equipment.

³ Maximum payload capacity includes weight of driver, passengers, optional equipment, upfitter installed body and equipment and cargo. Cargo and load capacity is limited by gross front and rear axle weight ratings and GVWR.

⁴ Fuel capacity is approximate.