

Shuttle Application



Vehicles shown have been altered or upfitted with equipment supplied by independent suppliers. See the Owner Manual for information on alterations and warranties.

GM provides the Commercial Cutaway Express/Savana 3500 and 4500 Chassis to support shuttle applications. This provides shuttle bus manufacturers the newest and most capable platforms.

The Express/Savana Cutaway Chassis, with a choice of wheelbases and GVWRs, can be upfit with shuttle bodies from a variety of manufacturers for greater seating capacity than standard passenger vans.

See the Powertrain Combinations chart for applicable engines and transmissions.

Model	Cab or Equipment	WB/CA (inches)	Drive Axle(s)/Rear Wheels	Body Length (feet)				Engine	GVWR (pounds)*	Max. Body and Payload (pounds)**
				8	10	12	14			
Express/Savana 3500	Commercial Cutaway w/ANC Shuttle Bus Package	139/80	2WD/SRW	■	■	■		L96	9900	5444
		139/80	2WD/SRW	■	■	■		LGH	9900	4754
		139/80	2WD/DRW				■	L96	10000	5129
		139/80	2WD/DRW				■	LGH	10000	4545
		139/80	2WD/DRW				■	L96	12300	7738
		139/80	2WD/DRW				■	LGH	12300	6838
		159/100	2WD/DRW				■	L96	10000	5169
		159/100	2WD/DRW				■	LGH	10000	4483
		159/100	2WD/DRW				■	L96	12300	7383
		159/100	2WD/DRW				■	LGH	12300	6697
Express/Savana 4500	Commercial Cutaway w/ANC Shuttle Bus Pkg	159/100	2WD/DRW				■	L96	14200	9149
		159/100	2WD/DRW				■	LGH	14200	8277

* When properly equipped; includes weight of vehicle, passengers, cargo and equipment.

** When properly equipped; maximum payload capacity includes weight of driver, passengers, optional equipment and cargo.