

## Canyon/Colorado

### Available Chassis Cab Models

- 2WD Chassis Cab (CS15603/TS15603)
- 4WD Chassis Cab (CT15603/TT15603)

### Engine

LLR	3.7L DOHC, 5-cylinder., MFI 242 horsepower, 242 lb.-ft. torque
-----	---

Model	Engine	Transmissions	Axle	GVWR* (pounds)
		4-Speed Automatic with OD (M30)	3.73 (GT4)	5300 (C3H)
CS15603/ TS15603/ CT15603/ TT15603	3.7L I-5 (LLR)	S	S	S

S = Standard Equipment

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Silverado/Sierra 1500

### Available Models, with Snow Plow Prep Package

- 4WD Regular Cab Standard Box (CK10703/TK10703)
- 4WD Regular Cab Long Box (CK10903/TK10903)

### Engines, with Snow Plow Prep Package

LY2	Vortec 4.8L V8 SFI 295 horsepower, 305 lb.-ft. torque
LY5	Vortec 5.3L V8 SFI Active Fuel Management™ 315 horsepower, 338 lb.-ft. torque
LMG	Vortec 5.3L V8 SFI, Active Fuel Management™, FlexFuel 315 horsepower, 338 lb.-ft. torque

Model	Engine	Transmissions	Axles			GVWR* (pounds)	
		4-Speed Automatic with OD (M30)	3.42 (GU6)	3.73 (GT4)	4.10 (GT5)	6400 (C7H)	6800 (CSU)
CK10*03/ TK10*03	4.8L V8 (LR4)	S	A	—	A <sup>1</sup>	S	A
CK10*03/ TK10*03	5.3L V8 (LY5)	S	—	A	A <sup>1</sup>	S	A
CK10*03/ TK10*03	5.3L V8 (LMG)	S	—	A	A <sup>1</sup>	S	A

S = Standard Equipment A = Available — = Not Available

1. Requires (G80) heavy-duty automatic locking rear differential.

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Silverado/Sierra 2500HD

### Available Models, with Pickup Box Delete

- 2WD Regular Cab (CC20903/TC20903)
- 2WD Extended Cab (CC20953/TK20953)
- 2WD Crew Cab (CC20943/TK20943)
- 4WD Regular Cab (CK20903/TK20903)
- 4WD Extended Cab (CK20953/TK20953)
- 4WD Crew Cab (CK20943/TK20943)

### Engines with Pickup Box Delete

LY6	Vortec 6.0L V8 SFI 353 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible 365 horsepower, 660 lb.-ft. torque

### Available Models, with Snow Plow Prep Package

- 4WD Regular Cab Long Box (CK20903/TK20903)
- 4WD Extended Cab Standard Box (CK20753/TK20753)
- 4WD Extended Cab Long Box (CK20953/TK20953)
- 4WD Crew Cab Standard Box (CK20743/TK20743)
- 4WD Crew Cab Long Box (CK20943/TK20943)

### Engines with Snow Plow Prep Package

LY6	Vortec 6.0L V8 SFI 353 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible (not available on CK20943/TK20943 4WD Crew Cab) 365 horsepower, 660 lb.-ft. torque

Model	Engine	Transmissions		Axles		GVWR* (pounds)
		6-Speed Automatic HD (MYD)	Allison 1000 6-Speed Automatic (MW7)	3.73 (GT4)	4.10 (GT5)	
CC20**3/ TC20**3	6.0L V8 (LY6)	S	—	S	A	S
CK20**3/ TK20**3	6.6L V8 (LMM)	—	A	S	—	S

S = Standard Equipment A = Available — = Not Available

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Silverado/Sierra 3500HD

### Available Models, with Pickup Box Delete

- 2WD Regular Cab Long Box with Single Rear Wheel only (CC30903/TC30903)  
– Standard with Pickup Box Delete
- 2WD Extended Cab Long Box with Single or Dual Rear Wheel (CC30953/TC30953)
- 2WD Crew Cab Long Box with Single or Dual Rear Wheel (CC30943/TC30943)
- 4WD Regular Cab Long Box with Single or Dual Rear Wheel (CK30903/TK30903)
- 4WD Extended Cab Long Box with Single or Dual Rear Wheel (CK30953/TK30953)
- 4WD Crew Cab Long Box with Single or Dual Rear Wheel (CK30943/TK30943)

### Engines with Pickup Box Delete

LY6	Vortec 6.0L V8 SFI 353 horsepower, 373 lb.-ft. torque (under 10,000 GVWR*) 312 horsepower, 373 lb.-ft. torque (over 10,000 GVWR*)
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible (not available on CC30903/TC30903) 365 horsepower, 660 lb.-ft. torque

### Available Models, with Snow Plow Prep Package

- 4WD Regular Cab Long Box (CK30903/TK30903)
- 4WD Crew Cab Long Box (CK30943/TK30943)
- 4WD Extended Cab Long Box (CK30953/TK30953)

### Engines with Snow Plow Prep Package

LY6	Vortec 6.0L V8 SFI 353 horsepower, 373 lb.-ft. torque (under 10,000 GVWR*) 312 horsepower, 373 lb.-ft. torque (over 10,000 GVWR*)
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible (not available on Extended Cab or Crew Cab models) 365 horsepower, 660 lb.-ft. torque

Model	Engine	Transmissions		Axles		GVWR* (pounds)		
		6-Speed Automatic HD (MYD)	Allison 6-Speed Automatic (MW7)	3.73 (GT4)	4.10 (GT5)	9700 (GED)	9900 (C4M)	11400 (C7W)
CC30903/TC30903	6.0L V8 (LY6)	S	—	S	A	S	—	—
CK30903/TK30903 CC30943/TC30943	6.0L V8 (LY6)	S	—	S	A	—	A	A
CC30953/TC30953 CK30943/TK30943 CK30953/TK30953	6.6L V8 <sup>1</sup> (LMM)	—	A	S	—	—	A	A

S = Standard Equipment A = Available — = Not Available

1. Not available on Extended or Crew Cab.

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Silverado/Sierra 3500 Chassis Cab

### Available Models

- 2WD Regular Cab SWB (CC31003/TC31003)
- 2WD Regular Cab LWB (CC31403/TC31403)
- 2WD Extended Cab SWB (CC31053/TC31053)
- 4WD Regular Cab SWB (CK31003/TK31003)
- 4WD Regular Cab LWB (CK31403/TK31403)
- 4WD Extended Cab SWB (CK31053/TK31053)

### Engines

LY6	Vortec 6.0L V8 SFI 312 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible 365 horsepower, 660 lb.-ft. torque

## Silverado/Sierra 3500 Chassis Cab with YF2 Ambulance Package

### Available Models

- 2WD Regular Cab, 161.5-inch wheelbase (CC31403/TC31403)
- 4WD Regular Cab, 161.5-inch wheelbase (CK31403/TK31403)

### Engines

LY6	Vortec 6.0L V8 SFI 312 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8; Biodiesel compatible 365 horsepower, 660 lb.-ft. torque

Model	Engine	Transmissions		Axles		GVWR* (pounds)	
		6-Speed Automatic HD (MYD)	Allison 1000 6-Speed Automatic with OD (MW7)	3.73 (GT4)	4.10 (GT5)	11,400 (C7W)	12,000 (C7L)
CC31**3/ TC31**3	6.0 L V8 (LY6)	S	—	S	A	S	—
	6.6L V8 (LMM)	—	A	S	—	S	—
CK31**3/ TK31**3	6.0 L V8 (LY6)	S	—	S	A	—	S
	6.6L V8 (LMM)	—	A	S	—	—	S

S = Standard Equipment A = Available — = Not Available

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Express/Savana Cargo Vans

### Available Models

- 135-inch wheelbase G1500 Cargo Van (CGI13405/TH13405)
- 135-inch wheelbase G1500 AWD Cargo Van (CHI13405/TH13405)
- 135-inch wheelbase G2500 Cargo Van (CGI23405/TH23405)
- 155-inch wheelbase G2500 Cargo Van (CGI23705/TH23705)
- 135-inch wheelbase G3500 Cargo Van (CGI33405/TH33405)
- 155-inch wheelbase G3500 Cargo Van (CGI33705/TH33705)

### Engines

LU3	Vortec 4.3L V6 MFI 195 horsepower, 260 lb.-ft. torque
LY2	Vortec 4.8L V8 SFI 279 horsepower, 294 lb.-ft. torque (under 10,000 lb. GVWR*) 258 horsepower, 294 lb.-ft. torque (over 10,000 lb. GVWR*)
LMF	Vortec 5.3L V8 SFI; FlexFuel available 301 horsepower, 325 lb.-ft. torque
LY6	Vortec 6.0L V8 SFI 323 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8 250 horsepower, 460 lb.-ft. torque

Model	Engine	Transmissions			Axles			GVWR* (pounds)		
		4-Speed Automatic (M30)	4-Speed Automatic HD (MT1)	4-Speed Automatic (MN8)	3.42 (GU6)	3.73 (GT4)	4.10 (GT5)	7200 (C5Z)	8600 (C6P)	9600 (C6Y)
<b>1500</b>										
CGI13405/ TH13405/	4.3L V6 (LU3) <sup>1</sup>	S	—	—	S	—	—	S	—	—
CHI13405/ TH13405	5.3L V8 (LMF)	S	—	—	S	A	—	S	—	—
<b>2500</b>										
CGI23405/ TH23405/	4.8L V8 (LY2)	—	S	—	—	S	A	—	S	—
CGI23705/ TH23705	6.0L V8 (LY6)	—	S	—	—	S	A	—	S	—
	6.6L V8 (LMM)	—	—	S	—	S	—	—	S	—
<b>3500</b>										
CGI33405/ TH33405/	4.8L V8 (LY2)	—	S	—	—	S	A	—	—	S
CGI33705/ TH33705	6.0L V8 (LY6)	—	S	—	—	S	A	—	—	S
	6.6L V8 (LMM)	—	—	S	—	S	—	—	—	S

S = Standard Equipment A = Available — = Not Available

1. Not available with All-Wheel Drive (AWD).

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Express/Savana Passenger Vans

### Available Models

- 135-inch wheelbase 1500 Passenger Van (CGI13406/TH13406)
- 135-inch wheelbase 1500 AWD Passenger Van (CHI13406/TH13406)
- 135-inch wheelbase 2500 Passenger Van (CHI23406/TH23406)
- 135-inch wheelbase 3500 Passenger Van (CGI33406/TH33406)
- 155-inch wheelbase 3500 Passenger Van (CGI33706/TH33706)

### Engines

LMF	Vortec 5.3L V8 SFI; FlexFuel available 301 horsepower, 325 lb.-ft. torque
LY6	Vortec 6.0L V8 SFI 323 horsepower, 373 lb.-ft. torque

Model	Engine	Transmissions		Axle	GVWR* (pounds)		
		4-Speed Automatic (M30)	4-Speed Automatic HD (MT1)		3.73 (GT4)	7200 (C5Z)	8600 (C6P)
<b>1500</b>							
CGI13406/ TH13406/ CHI13406/ TH13406	5.3L V8 (LMF)	S	—	S	S	—	—
<b>2500</b>							
CGI23406/ TH23406	6.0L V8 (LY6)	—	S	S	—	S	—
<b>3500</b>							
CGI33406/ TH33406/ CGI33706/ G33706	6.0L V8 (LY6)	—	S	S	—	—	S

S = Standard Equipment A = Available — = Not Available

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

## Express/Savana Cutaway

### Available Models

- 139-inch wheelbase Cutaway Van (CGI33503/TH33503)
- 159-inch wheelbase Cutaway Van (CGI33803/TH33803)
- 177-inch wheelbase Cutaway Van (CGI33903/TH33903)

### Engine RPOs

LY2	Vortec 4.8L V8 SFI 279 horsepower, 294 lb.-ft. torque (under 10,000 lb. GVWR) 258 horsepower, 294 lb.-ft. torque (over 10,000 lb. GVWR)
LY6	Vortec 6.0L V8 SFI 323 horsepower, 373 lb.-ft. torque
LMM	Duramax 6.6L Turbo Diesel V8 250 horsepower, 460 lb.-ft. torque

Model	Engine	Transmissions		Axles		GVWR* (pounds)			
		4-Speed Automatic HD (MT1)	4-Speed Automatic (MN8)	3.73 (GT4)	4.10 (GT5)	9600 (C7Y)	10000 (C7A)	12300 (C7N)	14050 (C7F)
CGI33503/ TH33503	4.8L V8 (LY2)	S	—	—	S	S <sup>1</sup>	A <sup>2</sup>	—	—
	6.0L V8 (LY6)	S	—	—	S	S <sup>1</sup>	A <sup>2</sup>	A <sup>2</sup>	—
	6.6L V8 (LMM)	—	S	S	—	S <sup>1</sup>	A <sup>2</sup>	A <sup>2</sup>	—
CGI33803/ TH33803	6.0L V8 (LY6)	S	—	—	S	—	S <sup>2</sup>	A <sup>2</sup>	A <sup>3</sup>
	6.6L V8 (LMM)	—	S	S	—	—	S <sup>2</sup>	A <sup>2</sup>	—
CGI33903/ TH33903	6.0L V8 (LY6)	S	—	—	S	—	—	A <sup>2</sup>	—
	6.6L V8 (LMM)	—	S	S	—	—	—	A <sup>2</sup>	—

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.

1. Requires (R04) Single Rear Wheels.

2. Requires (R05) Dual Rear Wheels.

3. Requires (YF1) RV Package and (R05) Dual Rear Wheels.

S = Standard Equipment

A = Available

— = Not Available

## Kodiak/TopKick C4500

### Available Models and Base GVWR Specifications

Model	Description	Base GVWR* (pounds)	Front GAWR (pounds)	Rear GAWR (pounds)
C4C042	2WD Regular Cab	16,500	7000	11,000
C4C044	4WD Regular Cab	17,500	8000	13,500
C4E042	2WD Crew Cab	16,500	8000	11,000
C4E044	4WD Crew Cab	17,500	7000	13,500
C4U042	2WD Motor Home	16,500	7000	11,000
C4V042	2WD Commercial Cutaway	16,500	7000	11,000

### Base Engine

LRW	Vortec 8.1L MD Gasoline V8 325 horsepower @ 4000 rpm, 450 lb.-ft. torque @ 2800 rpm Maximum engine speed 5000 rpm
-----	---

### Available Engines

LMM/LRX	Duramax Turbo Diesel 6.6L V8 300 horsepower @ 3000 rpm, 520 lb.-ft. torque @ 1600 rpm
LMM/LYE	Duramax Turbo Diesel 6.6L V8 330 horsepower @ 3000 rpm, 620 lb.-ft. torque @ 1600 rpm

\* When properly equipped; includes weight of vehicle, passengers, cargo, and equipment.

### Transmission Descriptions

- MBV:** Allison 1000 Series 6-speed with 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 620 lb.-ft. (840 N-m) with shift energy management. Column shift and parking pawl. Base model does not include power take-off gear. To include PTO gear, order with RPO "PTO". PTO mounting location on the driver's side. Includes transmission oil cooler located inside radiator. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission. (Not available with ANM Fire and Rescue Package or YF2 Ambulance Package)
- MBW:** Allison 1000EVS 6-speed: Automatic with 0.61 overdrive. Torque Rating: 650 lb.-ft. (766 N-m). Column shift and parking pawl. For emergency vehicle and ambulance. (Requires diesel engine)
- MHE:** Allison 2350 Series 6-speed with 4th Generation Electronic Controls with 0.61 overdrive. Torque Rating: 620 lb.-ft. (840 N-m). Available for general use for a Gross Vehicle Weight\* from 30,000 pounds (13,600 kg). Column shift and Parking pawl. Base model does not include power take-off gear, to include PTO gear, order with RPO "PTO". PTO mounting location on is on the driver's side. Includes transmission oil cooler located inside radiator. With Option PTX, the truck will be equipped with the Allison 2350HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 2350RDS Rugged Duty Series transmission. (Requires L18 gas engine or LYE diesel engine power option and 17500 lb. GVWR\*)

*Transmission Descriptions continued on next page.*

## Kodiak/TopKick C4500

### Transmission Descriptions (continued)

- **MTR:** Allison 1000MH Series (Close Ratio) 6-speed with 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 620 lb.-ft. (840 N-m) with shift energy management. Column shift and Park Pawl. Includes transmission oil cooler located inside radiator. For motor home application only (Requires C4U042 model only.)
- **MBX:** Allison 1000PTS Pupil Transportation/Shuttle Series 6-speed and 0.61 overdrive. Torque Rating: 565 lb.-ft. (766 N-m). Column shift and park pawl. (Requires ANC Shuttle Bus or B3D School Bus packages. Requires LRW gas engine or LRX diesel engine power option. Not available with PTO power-take-off provisions.)

### Axle Descriptions

- **GL4:** Single speed; 11,000-pound (4990 kg) capacity; full-floating
- **HD2:** Dana S110; 13,500-pound (6123 kg) capacity; full-floating

Model	Axle	Axle Ratio					
		5.13:1	4.30:1 <sup>2</sup>	4.56:1 <sup>3</sup>	4.63:1 <sup>4</sup>	4.78:1 <sup>3</sup>	4.88:1 <sup>5</sup>
C4C042	GL4 - S	S <sup>1</sup>	A	—	A	—	A
	HD2 - A	—	—	A	—	A	—
C4C044	HD2 - S	S	—	—	—	—	—
C4E042	GL4 - S	S <sup>1</sup>	A	A	A	—	A
	HD2 - A	—	—	—	—	A	—
C4E044	HD2 - S	S	—	—	—	—	—
C4U042	GL4 - S	S <sup>1</sup>	A	—	A	—	A
	HD2 - A	—	—	A	—	A	—
C4V042	GL4 - S	S <sup>1</sup>	A	—	A	—	A
	HD2 - A	—	—	A	—	A	—

S = Standard Equipment A = Available — = Not Available

1. Not recommended for most applications. Requires gasoline engine.
2. Requires diesel engine.
3. Requires HD2 axle.
4. Requires gas engine and GL4 axle.
5. Requires GL4 axle.

\*When properly equipped, includes weight of vehicle, passengers, cargo and equipment.