



2018 model shown. Vehicle shown with equipment from an independent supplier and is not covered by the GM New Vehicle Limited Warranty. GM is not responsible for the safety and quality of independent supplier alterations.

2019

AMBULANCE APPLICATION

UPFIT

FLEET MANAGEMENT

Body-on-frame (BOF) architecture helps provide a solid vehicle foundation for various upfits

POWER

DRIVER PRODUCTIVITY

Dual batteries, with an isolated second battery, help power equipment on van models

VARIETY

FLEET MANAGEMENT

Chassis Cab, Cargo Van and Van Cutaway models provide options for emergency service vocations

AVAILABLE MODELS

Silverado/Sierra 3500HD Chassis Cab	1WT/1LT
Express/Savana Cargo Van RWD 3500 - Extended	1WT
Express/Savana Cutaway RWD 3500 - 139-inch wheelbase	1WT
RWD 3500 - 159-inch wheelbase	1WT
RWD 4500 - 159-inch wheelbase	2WT

EXTERIOR COLORS

Cardinal Red	Dark Sky Metallic ¹	Marine Blue Metallic ¹
		
Onyx Black	Quicksilver Metallic ¹	Summit White
		

AMBULANCE PACKAGES

SILVERADO/SIERRA REGULAR CAB/CHASSIS CAB

Requires fleet or government sales order type.

Duramax® 6.6L Turbo-Diesel engine (445 hp/910 lb.-ft.)
Allison® 6-speed automatic transmission
Alternator options: Single 150-amp, Single 220-amp or Dual 220-/150-amp
Wide-track rear axle

EXPRESS/SAVANA CARGO VANS (YF2)

Requires 3500 Extended Wheelbase model and specific glass packages. See Order Guide for details.

4.3L V6 engine (276 hp/298 lb.-ft.)
8-speed automatic transmission
220-amp alternator
Chrome Appearance Package
Dual batteries: 770 cold-cranking amp primary and isolated heavy-duty 770 cold-cranking amp (late availability)
Dual-note horn
High idle switch
HVAC system auxiliary provisions
Locking rear differential
Wiring provisions for electrical accessories

EXPRESS/SAVANA CUTAWAY (YF2)

Requires 3500 with 139-inch or 159-inch wheelbase or 4500 model with 159-inch wheelbase.

6.0L V8 engine (341 hp/373 lb.-ft.)
6-speed automatic transmission
33- or 57-gallon fuel tank
220-amp alternator
Chrome Appearance Package
Dual batteries: 770 cold-cranking amp primary and isolated heavy-duty 770 cold-cranking amp (late availability)
Dual-note horn
Dual rear wheels
High idle switch
HVAC system auxiliary provisions
Light package with separate stop/turn circuits
Locking rear differential
Wiring provisions for electrical accessories

	3500 Cargo Van	3500 Cutaway Van	4500 Cutaway Van	3500 Regular Cab Chassis Cab
Powertrain/Mechanical				
Standard engine	4.3L V6 6.0L V8 (available)	6.0L V8	6.0L V8	6.6L Turbo-Diesel V8
Transmission	8-speed	6-speed	6-speed	Allison® 6-speed
Frame yield strength (psi)	33,000	33,000	33,000	33,000
GVWR ² (lbs.)	9,600	12,300	14,200	13,200
Max. payload ³ (lbs.)	4,066	7,496 (139-in. WB)/ 7,281 (159-in. WB)	9,006	6,262 (2WD)/ 6,050 (4WD)
Max. fuel tank capacity (gal.)	31	33/57	57	63.5
Exterior Dimensions				
Wheelbase (in.)	155	139/159	159	162
Length (in.)	244.1	246.7/266.7	266.7	254
Height (in.)	84.1	82.9	82.9	76.5
Body width (in.)	79.2	79.2	79.2	80.1
Cab-to-axle (in.)	—	80/100	100	83.6
Cab to end of frame (in.)	—	148.5/168.5	168.5	134.5
Ground clearance (front/rear) (in.)	8.8/7.7	7.6/7.0	7.6/7.0	8.9/8.6

1 Premium paint; additional charge. **2** Maximum Gross Vehicle Weight Rating (GVWR). When properly equipped; includes weight of vehicle, passengers, cargo and equipment. **3** These maximum payload ratings are intended for comparison purposes only. Before you buy a vehicle or use it to haul people or cargo, carefully review the Vehicle Loading section of the Owner's Manual and check the carrying capacity of your specific vehicle on the label on the inside of the driver's door jamb.